

# Cat Tail.01

HodgePodge



Published: January 2026
















## Cat Tail.01

### Product Specification

The full-size Cat Tail.01 sways to and fro all the time ... hey, it's a cat tail! The Cat Tail has a body and a stem made out of stainless steel. The curved stem and the bi-colored HDPE-platform turns a piece of play equipment into an eye-catcher for all public places in town.

# Cat Tail.01

## 90.260.201

	Product Family	<b>HodgePodge</b>
	Length x Width x Height (m) Length x Width x Height ("")	<b>0,8 x 0,4 x 2,5</b> <b>2-5 x 1-1 x 8-3</b>
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	<b>3,6 x 3,6</b> <b>4,3 x 4,3</b> <b>14-0 x 14-0</b>
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	<b>0,40</b> <b>1-4</b>
	Age	<b>5</b>
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	<b>10,2</b> <b>153,3</b>
	Number of Foundations	<b>1</b>
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	<b>0,5</b> <b>17,7</b>
	Number of skilled Installers required	<b>2</b>
	Installation Time without Foundation	<b>2 hours</b>
	Dimensions of largest Part (m) Dimensions of largest Part ("")	<b>0,7 x 0,4 x 2,9</b> <b>2-4 x 1-4 x 9-7</b>
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	<b>55,0</b> <b>121,3</b>
	Shipping Volume (m³) Shipping Volume (ft³)	<b>1,7</b> <b>60,1</b>
	Total Weight (kg) Total Weight (lbs)	<b>85,0</b> <b>187,4</b>
	Spare Part Guarantee	<b>Lifelong</b>

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

## Technical Data

Technical changes are reserved.  
The following text can also be used for tenders.

### Base plate:

Stainless steel plate Ø 320 mm (1'-1"), covered with 19 mm (3/4") thick HDPE panels to ensure durability, deter vandalism, and to remain structurally sound for generations. The sturdy material helps to prevent cracks and breaks. Extremely UV-resistant and color-proof. All edges are rounded.

### Tubes:


Framework®- stainless steel tubes, Ø 48,3 & 40,0 mm (1'-7/8" & 1'-9/16"), slightly bent, grounded and polished. Connected to an Framework®-aluminum ball connector.

### Luffing Mechanism:

Fully encapsulated rubber-metal-bearing integrated in stainless steel foundation tube.

### Sphere:

Framework®- aluminum ball connectors, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The tensioning ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.



1:200