Little Big Ben.2.2

HodgePodge

Published: January 2026

Little Big Ben.2.2

Product Specification

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, Wasps' nest, zip lines, swings and carousels for fun and excitement.

A ride on the Little Big Ben is a great experience, as the speed of spinning depends on how its users work together – every ride is a unique adventure.

Berliner

Play equipment for life

Little Big Ben.2.2

90.260.305

Product Family	**HodgePodge**
Length × Width × Height (m) Length × Width × Height ('-")	**1,3 × 1,3 × 0,9** **4-1 × 4-1 × 2-9**
Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-")	**5,3 × 5,3** **4,9 × 4,9** **16-1 × 16-1**
Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-")	**0,36** **1-3**
Age	**3**
Minimum Space required acc. to DIN EN 1176 (m^2) Minimum Space required acc. to ASTM 1487 (ft^2)	**21,5** **202,1**
Number of Foundations	**1**
Concrete Volume C20/C25 (m^3) Concrete Volume C20/C25 (ft^3)	**0,3** **10,6**
Number of skilled Installers required	**2**
Installation Time without Foundation	**1 hours**
Dimensions of largest Part (m) Dimensions of largest Part ('-")	**1,3 × 1,3 × 1,3** **4-4 × 4-4 × 4-4**
Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	**125,0** **275,6**
Shipping Volume (m^3) Shipping Volume (ft^3)	**2,9** **102,4**
Total Weight (kg) Total Weight (lbs)	**290,0** **639,3**
Spare Part Guarantee	**Lifelong**

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.
The safety surface must have shock-absorbing properties sufficient to protect against a fall from a height of at least 1000 mm.

1:200

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Turntable:
The stainless steel plate with a diameter of 1230 mm (4'-1") is covered with HDPE plates and surrounded by a welded stainless steel tube with a diameter of 60,3 mm (2 3/8").

Tubes:
Frameworx®- stainless steel tubes Ø 60,3 mm (2 3/8"), smoothed and brushed.

Spheres:
Frameworx®- aluminum ball connectors, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.

Stand:
The fully integrated bearing unit forms a self-contained system and is therefore particularly insensitive to weather influences and requires little maintenance.

Covering:
The non-skid HDPE plates with ae thickness of 19 mm (3/4") are screwed flat on the turntable.