

Swingo.2.4

HodgePodge



Published: February 2025

Swingo.2.4
















Product Specification


HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, Wasps' nest, zip lines, swings and carousels for fun and excitement.

The large two-bay-version of the Swingo combines asymmetry and high-ying-dynamics. Cool game – cool look!

Swingo.2.4

90.260.504

	Product Family	HodgePodge
	Length x Width x Height (m) Length x Width x Height ("')	5,9 x 2,5 x 3,4 19-4 x 8-2 x 11-0
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("')	8,8 x 3,1 10,7 x 9,6 34-11 x 31-4
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("')	1,67 9-7
	Age	5
	Minimum Space required acc. to DIN EN 1176 (m ²) Minimum Space required acc. to ASTM 1487 (ft ²)	27,3 664,6
	Number of Foundations	6
	Concrete Volume C20/C25 (m ³) Concrete Volume C20/C25 (ft ³)	0,9 31,8
	Number of skilled Installers required	2
	Installation Time without Foundation	2 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("')	0,1 x 0,5 x 4,0 0-4 x 1-8 x 13-2
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	48,0 105,9
	Shipping Volume (m ³) Shipping Volume (ft ³)	1,9 67,0
	Total Weight (kg) Total Weight (lbs)	290 640
	Spare Part Guarantee	Lifelong



1:200

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Framework:

Stainless steel tube bends Ø 60.3 mm (2 3/8"), connected to Frameworx®-aluminum ball connectors, Ø 250 mm (9-13/16"), anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process, securely closed with durable EPDM-caps.

Swing seat:

The black rubber safety swing seat is by stainless steel chains rotatable mounted to the cross tube mounted in maintenance free nylon bushes.

Spheres:

Frameworx®- aluminum ball connectors, Ø 250 mm (9 13/16"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.