

Fireball.2.2

HodgePodge



Published: January 2026

Fireball.2.2
















Product Specification

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, Wasps' nest, zip lines, swings and carousels for fun and excitement.

The Fireball.2.2 is the best place in town for those who love to get dizzy occasionally. The rotation axis is inclined at 2°. Move your body to and around the axis and you will feel what gravity is. The Fireball is absolutely strong enough for two or more users to take a spin.

Fireball.2.2

90.260.307.12

	Product Family	HodgePodge
	Length × Width × Height (m) Length × Width × Height ("-")	1,0 × 1,0 × 1,4 3-3 × 3-3 × 4-7
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("-")	5,0 × 5,0 4,7 × 4,7 15-3 × 15-3
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("-")	0,90 3-0
	Age	5-12
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	19,5 182,0
	Number of Foundations	1
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	0,5 17,7
	Number of skilled Installers required	2
	Installation Time without Foundation	1 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("-")	1,0 × 1,0 × 1,8 3-4 × 3-4 × 5-11
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	110,0 242,5
	Shipping Volume (m³) Shipping Volume (ft³)	3,1 109,5
	Total Weight (kg) Total Weight (lbs)	240,0 529,1
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.

The following text can also be used for tenders.

Turntable:

The stainless steel plate with a diameter of Ø 960 mm (3'-2") is covered with HDPE plates and surrounded by a welded stainless steel tube with a diameter of Ø 60,3 mm (2 3/8").

Tube:



Frameworkx®- stainless steel tube Ø 60,3 mm (2 3/8").

Sphere:

Frameworkx®- aluminum ball connectors, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.

Stand:

The fully integrated bearing unit forms a self-contained system and is therefore particularly insensitive to weather influences and requires little maintenance.



1:200