

Spoo M.06

Spooky Rookies



Published: May 2025

Spoo M.06

Product Specification

The playhouses in the Spooky Rookies product group are specifically designed to support the development of motor and psychomotor skills in toddlers aged 0 to 3 years. This makes them ideal for use in nurseries, daycare centers, and public playgrounds.
















Our adorable Spoo and Roo playhouses are available, as always, with a wide variety of add-on elements and in different combi-

nations. A range of play functions, such as a counter, mud table, tic-tac-toe, or a memory game, can be integrated.

This Spoo M.06 model features a platform height of 90 centimeters (2'-11 7/16"). Those who climb the ramp are rewarded with a quick descent down the slide. Thanks to the bamboo panels, the playhouse blends well into a natural environment.

Spoo M.06

90.295.100.6

	Product Family	Spooky Rookies
	Length × Width × Height (m) Length × Width × Height ("")	4,1 × 2,5 × 2,7 13-6 × 8-1 × 8-8
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	7,5 × 5,9 7,8 × 6,2 25-6 × 20-2
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	0,90 3-0
	Age	2 - 12
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	27,9 364,7
	Number of Foundations	7
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	0,6 21,2
	Number of skilled Installers required	3
	Installation Time without Foundation	6 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("")	0,6 × 1,0 × 3,0 2-0 × 3-4 × 9-11
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	75,0 165,3
	Shipping Volume (m³) Shipping Volume (ft³)	3,8 134,2
	Total Weight (kg) Total Weight (lbs)	1200,0 2645,5
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Posts:

Steel pipes Ø 101,6 mm (4"), wall thickness 4 mm (3/16") with a round cast aluminum post top, anti-corrosion treatment and colour finish: sandblasting and solvent-free epoxy-/ polyester-process.

Spheres:

Framework®- aluminum ball connectors, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.

Tube Framework:

A combination of straight and bended stainless steel Framework®- tubes, Ø 48 mm (1 7/8"), material AISI304 (DIN 1.4301). The tubes are connected to build a space framework with a triangular footprint.

Panels/Ramp:

HDPE-panel (roof and walls), thickness 19 mm (3/4"), panel connected to steel pipes (for more details, see members) with cast aluminum panel clamps; non-skid HPL-panel (bottom and ramp), thickness 19 mm (3/4").



1:200

Fast Lane Slide:

Straight box slide made of solid 19 mm (3/4") thick HDPE panels to ensure durability, deter vandalism, and to remain structurally sound for generations. The sturdy material helps to prevent cracks and breaks. Extremely UV-resistant and color-proof. All edges are rounded. The substructure is comprised of stainless steel tubes with a diameter of 60,3 mm (2 3/8").

Bamboo Panels:

Bamboo strips 90 mm (3 1/2") width, mounted on a supporting board made from HDPE, 19 mm (3/4") thickness, rounded edges. Mounted with cast aluminum clamps to the tubes of the framework.