

Wonderwalls.04

Spooky Rookies



Published: July 2025

Wonderwalls.04
















Product Specification

Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned

out around a central post. As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches, sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

Wonderwalls.04

95.191.146

	Product Family	Spooky Rookies
	Length x Width x Height (m) Length x Width x Height ("")	3,3 x 2,4 x 1,7 10-9 x 7-10 x 5-4
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	6,3 x 5,5 7,0 x 6,1 22-9 x 19-10
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	0,58 1-11
	Age	3
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	26,0 350,3
	Number of Foundations	5
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	2,1 74,2
	Number of skilled Installers required	3
	Installation Time without Foundation	8 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("")	1,2 x 2,4 x 0,1 4-0 x 7-11 x 0-4
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	55,0 121,3
	Shipping Volume (m³) Shipping Volume (ft³)	4,4 155,4
	Total Weight (kg) Total Weight (lbs)	675,0 1488,1
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Posts:

Steel pipes Ø 133 mm (5 1/4"), wall thickness 5 - 10 mm (3/16" - 3/8") with a round cast aluminum post top. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

Tubes:

Framework®- steel tubes, Ø 60,3 mm (2 3/8"). Anti-corrosion treatment and color finish: sandblasting, sensimir galvanised and solvent-free epoxy-/ polyester-process.

Terranos®- Clamps:


Two-part cast aluminum connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos®- steel posts. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

HDPE-Panels:

Wall, play and design elements are made of solid-coloured and grained HDPE panels with a thickness of 19 mm (3/4") and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminium panel clamps.

Ropes:

U-Rope®-round strand ropes with galvanized and covered wires. External strands with non-abrasive UV-resistant polyester-yarn (no polypropylene), Ø 16 mm (5/8").



1:200