

# Wonderwalls.04

Spooky Rookies



Published: July 2025

## Wonderwalls.04
















### Product Specification


Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned

out around a central post. As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches, sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

# Wonderwalls.04

95.191.146

	Product Family	<b>Spooky Rookies</b>
	Length × Width × Height (m) Length × Width × Height ("")	<b>3,3 × 2,4 × 1,7</b> <b>10-9 × 7-10 × 5-4</b>
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	<b>6,3 × 5,5</b> <b>7,0 × 6,1</b> <b>22-9 × 19-10</b>
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	<b>0,58</b> <b>1-11</b>
	Age	<b>2 - 5</b>
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	<b>26,0</b> <b>350,3</b>
	Number of Foundations	<b>5</b>
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	<b>2,1</b> <b>74,2</b>
	Number of skilled Installers required	<b>3</b>
	Installation Time without Foundation	<b>8 hours</b>
	Dimensions of largest Part (m) Dimensions of largest Part ("")	<b>1,2 × 2,4 × 0,1</b> <b>4-0 × 7-11 × 0-4</b>
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	<b>55,0</b> <b>121,3</b>
	Shipping Volume (m³) Shipping Volume (ft³)	<b>4,4</b> <b>155,4</b>
	Total Weight (kg) Total Weight (lbs)	<b>675,0</b> <b>1488,1</b>
	Spare Part Guarantee	<b>Lifelong</b>



1:200

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

## Technical Data

Technical changes are reserved.

The following text can also be used for tenders.

### Posts:

Steel pipes Ø 133 mm (5 1/4"), wall thickness 5 - 10 mm (3/16" - 3/8") with a round cast aluminum post top. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

### Tubes:

Framework®- steel tubes, Ø 60,3 mm (2 3/8"). Anti-corrosion treatment and color finish: sandblasting, sensimir galvanised and solvent-free epoxy-/ polyester-process.

### Terranos®- Clamps:

Two-part cast aluminum connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos®- steel posts. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

### HDPE-Panels:

Wall, play and design elements are made of solid-coloured and grained HDPE panels with a thickness of 19 mm (3/4") and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminium panel clamps.

### Ropes:

U-Rope®-round strand ropes with galvanized and covered wires. External strands with non-abrasive UV-resistant polyester-yarn (no polypropylene), Ø 16 mm (5/8").

### Jungle Bridge:

Bridge with thick walk rope comprised of Polypropylene-cordage, Ø 150 mm (5 7/8"), with steelcore Ø 12 mm (1/2").